



Subsidiary of MK Group

**MR GEARBOX AT FLUID
4HP-5HP 5L**



Product Description

Mr. GEAR BOX ATF 4HP-5HP is crafted with a blend of high-viscosity index synthetic base stocks and cutting-edge additive technology, designed to meet the rigorous demands of automatic gearboxes in passenger vehicles. It delivers top-tier performance across a diverse spectrum of automatic transmission standards and offers exceptional reliability in North American, European, and Asian automobiles. Specifically engineered for 4 and 5-speed automatic transmissions.

Recommended for use in all GM vehicles DII, DIII(G), DIII(H), this fluid surpasses industry standards including JASO 1A, Ford M, and Allison C-4 fluid specifications, making it an ideal choice for transmissions requiring Toyota Type T-IV fluid.

Applications / Benefits

- ✓ Delivers superior friction, oxidation, and thermal stability
- ✓ Exceptional anti-wear properties
- ✓ Enhances hydrolytic stability
- ✓ Superior cold temperature flow properties

ISSUED BY MR GEARBOX PTE. LTD.

TEL: (65) 6264 3832

[Https://gearbox.sg](https://gearbox.sg)

Furnishing the information contained herein Mr. Gearbox hereby asserts that neither the provision of information nor any actions taken by Mr. Gearbox shall be construed as an assertion that any product or process is exempt from potential claims of patent infringement by any third party, nor shall it be considered as conferring a license under any patent owned by Mr. Gearbox or any third party. Mr. Gearbox disclaims any responsibility for any infringement that may arise from the use of its products. The information and recommendations provided herein are believed to be accurate and reliable to the best of our knowledge, but they should not be regarded as definitive recommendations. Users are strongly advised to conduct their own tests to determine the suitability of the products for their particular purposes. Mr. Gearbox warrants only that its products meet the specifications outlined for them and explicitly disclaims all other warranties, whether express or implied, including but not limited to warranties of MERCHANTABILITY and FITNESS for a particular purpose.



Subsidiary of MK Group

MR GEARBOX AT FLUID 4HP-5HP 5L



Typical Characteristics

Test Description	Method	Unit	TASA	DEXRON IID	DEXRON III G/H
Density @ 15 °C	ASTM D 4052	kg/L	0.856	0.854	0.853
Flash Point	ASTM D 92	°C	200	198	194
Pour Point	ASTM D 97	°C	-33	-36	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	40.2	37	35.7
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	7.7	7.4	7.3
Viscosity Index	ASTM D 2270	-	166	170	175
Appearance	Visual	-	Red	Red	Red

Specifications, Approvals & Recommendations

	TASA	DEXRON II D	DEXRON III G/H
* ALLISON	-	-	C4
* FORD	-	-	FORD M
* FORD	-	FORD ESP-M2C166-H	FORD ESP-M2C166-H
* FORD	-	FORD ESP-M2C138-CJ	FORD ESP-M2C138-CJ
* GM	-	-	D-IIIIH
* GM	-	D-IIID	D-IIID
* GM	TASA	TASA	TASA
* MB	-	236.2	236.2

ISSUED BY MR GEARBOX PTE. LTD.

TEL: (65) 6264 3832

<https://gearbox.sg>

Furnishing the information contained herein Mr. Gearbox hereby asserts that neither the provision of information nor any actions taken by Mr. Gearbox shall be construed as an assertion that any product or process is exempt from potential claims of patent infringement by any third party, nor shall it be considered as conferring a license under any patent owned by Mr. Gearbox or any third party. Mr. Gearbox disclaims any responsibility for any infringement that may arise from the use of its products. The information and recommendations provided herein are believed to be accurate and reliable to the best of our knowledge, but they should not be regarded as definitive recommendations. Users are strongly advised to conduct their own tests to determine the suitability of the products for their particular purposes. Mr. Gearbox warrants only that its products meet the specifications outlined for them and explicitly disclaims all other warranties, whether express or implied, including but not limited to warranties of MERCHANTABILITY and FITNESS for a particular purpose.