


MR GEARBOX ATFFLUID DCTF EURO-ASIA 5L





Product Description

Mr. GEAR BOXATF DCTF EURO-ASIA is a high-quality synthetic transmission fluid engineered for optimal performance. It features high viscosity index synthetic base oils and cutting-edge additives such as friction modifiers, detergent dispersants, oxidation inhibitors, viscosity index enhancers, corrosion inhibitors, and defoamers. This formulation provides outstanding oxidation resistance, friction stability, anti-wear characteristics, and excellent low-temperature fluidity, making it perfect for modern, advanced vehicles.

Mr. GEAR BOX ATF MV DCTF is compatible with VW, Seat, and Skoda 6-speed wet Dual Clutch Transmissions (from 2003 onwards), as well as Ford, Volvo, Mitsubishi, PSA, and Chrysler 6-speed wet Dual Clutch Transmissions (from 2007 onwards)

Applications / Benefits

- Offers exceptional oxidation and thermal stability for extended longevity.
- Delivers superior wear protection to safeguard critical transmission components. Maintains excellent viscosity stability (high VI).
- Significantly improves fluidity in very low-temperature conditions.

ISSUED BY MR GEARBOX PTE. LTD.

TEL: (65) 6264 3832

Https://gearbox.sg

Furnishing the information contained herein Mr. Gearbox hereby asserts that neither the provision of information nor any actions taken by Mr. Gearbox shall be construed as an assertion that any product or process is exempt from potential claims of patent infringement by any third party, nor shall it be considered as conferring a license under any patent owned by Mr. Gearbox or any third party. Mr. Gearbox disclaims any responsibility for any infringement that may arise from the use of its products. The information and recommendations provided herein are believed to be accurate and reliable to the best of our knowledge, but they should not be regarded as definitive recommendations. Users are strongly advised to conduct their own tests to determine the suitability of the products for their particular purposes. Mr. Gearbox warranties only that its products meet the specifications outlined for them and explicitly disclaims all other warranties, whether express or implied, including but not limited to warranties of MERCHANTABILITY and FITNESS for a particular purpose.




MR GEARBOX ATFFLUID DCTF EURO-ASIA 5L



Typical Characteristic

Test Description	Method	Unit	
D :: 0.4500	4 OT 1 A D 4 O F O		0.045
Density @ 15 °C	ASTM D 4052	kg/L	0.845
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	32.9
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	7.17
Viscosity Index	ASTM D 2270	-	190
Brookfield Viscosity @ -40°C	ASTM D2983	mPa.s	8572





MR GEARBOX ATFFLUID **DCTF EURO-ASIA 5L**

Specifications, Approvals & Recommendations

ОЕМ	Vehicle Model*	Transmissions	Specifications*
Audi	A3, TT	DQ250, DQ500	VW TL 052 182
Audi	-	DQ400E (Hybrid)	-
BMW (Getrag)	1, 3, 5, 6 series, Z4, X1	7DCI600	83 22 2 148 578 83 22 2 148 579 83 22 0 440 214 83 22 2 147 477
Ford / Getrag	Fiesta, Focus, Mondeo, B-Max, C-Max, S-Max, Galaxy, Transit	6DCT450, 7DCT300	Ford M2C936A
Geely	-	7DCT330F	-
Geely	-	7DCT390H (Hybrid)	-
Great Wall	-	7DCT300	-
Magna	-	7DCI600	-
Magna	-	7DCT300	-
Mercedes-Benz	A-Class, B-Class	F-DCT350, F-DCT500	MB 236.21
Seat	Ibiza, Toledo, Leon, Altea	DQ250, DQ500	VW TL 052 182
Skoda	Fabia, Yeti, Octavia, Superb	DQ250, DQ500	VW TL 052 182
Volkswagen	Golf, Golf Plus, Eos, Scirocco, Caddy, Touran, Tiguan, Passat, Phideon, CC, Transporter, Sharan	DQ250, DQ500, DQ381	VW TL 052 182
Volvo	C30, S40, S60, V40, V50, V60, V70, S80, XC30, XC60	6DCT450	1161838 / 1161839

^{*} For reference only, please confirm correct application based on Transmission model as OEMs may have different transmission models in the same vehicle model type

ISSUED BY MR GEARBOX PTE. LTD. TEL: (65) 6264 3832 Https://gearbox.sg

Furnishing the information contained herein Mr. Gearbox hereby asserts that neither the provision of information nor any actions taken by Mr. Gearbox shall be construed as an assertion that any product or process is exempt from potential claims of patent infringement by any third party, nor shall it be considered as conferring a license under any patent owned by Mr. Gearbox or any third party, Mr. Gearbox disclaims any responsibility for any infringement that may arise from the use of its products. The information and recommendations provided herein are believed to be accurate and reliable to the best of our knowledge, but they should not be regarded as definitive recommendations. Users are strongly advised to conduct their own tests to determine the suitability of the products for their particular purposes. Mr. Gearbox warrants only that its products meet the specifications outlined for them and explicitly disclaims all other warranties, whether express or implied, including but not limited to warranties of MERCHANTABILITY and FITNESS for a particular purpose.