



Subsidiary of MK Group

**MR GEARBOX AT FLUID
5HP EURO 5L**



Product Description

Mr. GEAR BOX ATF 5HP EURO is crafted with a blend of high-viscosity index synthetic base stocks and cutting-edge additive technology, designed to meet the rigorous demands of automatic gearboxes in passenger vehicles. It delivers top-tier performance across a diverse spectrum of automatic transmission standards and offers exceptional reliability in North American, European. Specifically engineered for 4 and 5-speed automatic transmissions.

Recommended for use in all GM vehicles DII, DIII(G), DIII(H), this fluid surpasses industry standards including JASO 1A, Ford M, and Allison C-4 fluid specifications.

Applications / Benefits

- Offers excellent oxidation and thermal stability, ensuring longer life.
- Provides superior wear protection to safeguard critical transmission components.
- Maintains excellent viscosity stability (high VI), suitable for a wide range of auto transmissions.
- Delivers excellent friction and anti-shudder performance, enhancing driver comfort with smooth and efficient shifting.
- Significantly improves fluidity at very low temperatures.
- Provides outstanding rust and corrosion protection.

ISSUED BY MR GEARBOX PTE. LTD.

TEL: (65) 6264 3832

<https://gearbox.sg>

Furnishing the information contained herein Mr. Gearbox hereby asserts that neither the provision of information nor any actions taken by Mr. Gearbox shall be construed as an assertion that any product or process is exempt from potential claims of patent infringement by any third party, nor shall it be considered as conferring a license under any patent owned by Mr. Gearbox or any third party. Mr. Gearbox disclaims any responsibility for any infringement that may arise from the use of its products. The information and recommendations provided herein are believed to be accurate and reliable to the best of our knowledge, but they should not be regarded as definitive recommendations. Users are strongly advised to conduct their own tests to determine the suitability of the products for their particular purposes. Mr. Gearbox warrants only that its products meet the specifications outlined for them and explicitly disclaims all other warranties, whether express or implied, including but not limited to warranties of MERCHANTABILITY and FITNESS for a particular purpose.



Subsidiary of MK Group

**MR GEARBOX AT FLUID
5HP EURO 5L**



Typical Characteristic

Test Description	Method	
Specific Gravity @ 15 °C	ASTM D 4052	0.853
Flash Point, °C	ASTM D 92	198
Pour Point , °C	ASTM D 97	-45
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	38.1
cSt @ 100°C	ASTM D 445	7.24
Viscosity Index	ASTM D 2270	157
Color	ASTM D 1500	<2.5

Specifications, Approvals & Recommendations

- Esso LT 71141

ISSUED BY MR GEARBOX PTE. LTD.

TEL: (65) 6264 3832

[Https://gearbox.sg](https://gearbox.sg)

Furnishing the information contained herein Mr. Gearbox hereby asserts that neither the provision of information nor any actions taken by Mr. Gearbox shall be construed as an assertion that any product or process is exempt from potential claims of patent infringement by any third party, nor shall it be considered as conferring a license under any patent owned by Mr. Gearbox or any third party. Mr. Gearbox disclaims any responsibility for any infringement that may arise from the use of its products. The information and recommendations provided herein are believed to be accurate and reliable to the best of our knowledge, but they should not be regarded as definitive recommendations. Users are strongly advised to conduct their own tests to determine the suitability of the products for their particular purposes. Mr. Gearbox warrants only that its products meet the specifications outlined for them and explicitly disclaims all other warranties, whether express or implied, including but not limited to warranties of MERCHANTABILITY and FITNESS for a particular purpose.