



**MR GEARBOX CVTF
LINEARTRONIC 5L**



Subsidiary of MK Group



Product Description

Mr. GEAR BOX ATF 7G-9G is a top-tier synthetic automatic transmission fluid, formulated with high-quality synthetic base stocks and the latest additive technology. It excels in applications requiring low viscosity ATF, including Toyota Type WS, Nissan Matic S, Hyundai SP-IV, ZF M1375, DEXRON-VI, and MERCON LV.

ATF 7G-9G's synthetic base stocks and stability provide robust protection against thermal breakdown at high operating temperatures, while maintaining excellent performance at temperatures as low as -45°C. Furthermore, it enhances transmission durability and cleanliness, ensuring optimal long-term performance.

Applications / Benefits

- Offers superior friction, oxidation, and thermal stability.
- Delivers exceptional anti-wear properties and robust oil film thickness.
- Ensures excellent low-temperature fluidity, minimizing startup wear. Provides extended lifespan thanks to a fully synthetic base and carefully chosen additives.
- Maintains excellent shear stability for consistent performance
- Compatible with a wide range of seals.

ISSUED BY MR GEARBOX PTE. LTD.

TEL: (65) 6264 3832

[Https://gearbox.sg](https://gearbox.sg)

Furnishing the information contained herein Mr. Gearbox hereby asserts that neither the provision of information nor any actions taken by Mr. Gearbox shall be construed as an assertion that any product or process is exempt from potential claims of patent infringement by any third party, nor shall it be considered as conferring a license under any patent owned by Mr. Gearbox or any third party. Mr. Gearbox disclaims any responsibility for any infringement that may arise from the use of its products. The information and recommendations provided herein are believed to be accurate and reliable to the best of our knowledge, but they should not be regarded as definitive recommendations. Users are strongly advised to conduct their own tests to determine the suitability of the products for their particular purposes. Mr. Gearbox warrants only that its products meet the specifications outlined for them and explicitly disclaims all other warranties, whether express or implied, including but not limited to warranties of MERCHANTABILITY and FITNESS for a particular purpose.



MR GEARBOX CVTF LINEARTRONIC 5L



Subsidiary of MK Group



Typical Characteristic

Test Description	Method	
Specific Gravity @ 15 °C	ASTM D 4052	0.852
Flash Point, °C	ASTM D 92	198
Pour Point , °C	ASTM D 97	-45
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	33.1
cSt @ 100°C	ASTM D 445	7.1
Viscosity Index	ASTM D 2270	187
Viscosity, Brookfield @ -40°C mPa.s	ASTM D 2983	11260
Appearance	Visual	Bluish Green

Specifications, Approvals & Recommendations

- Subaru ECVT
- Subaru iCVT FG (K0414Y0710)
- Subaru Lineartronic CVTF (K0425Y0710)

ISSUED BY MR GEARBOX PTE. LTD.

TEL: (65) 6264 3832

[Https://gearbox.sg](https://gearbox.sg)

Furnishing the information contained herein Mr. Gearbox hereby asserts that neither the provision of information nor any actions taken by Mr. Gearbox shall be construed as an assertion that any product or process is exempt from potential claims of patent infringement by any third party, nor shall it be considered as conferring a license under any patent owned by Mr. Gearbox or any third party. Mr. Gearbox disclaims any responsibility for any infringement that may arise from the use of its products. The information and recommendations provided herein are believed to be accurate and reliable to the best of our knowledge, but they should not be regarded as definitive recommendations. Users are strongly advised to conduct their own tests to determine the suitability of the products for their particular purposes. Mr. Gearbox warrants only that its products meet the specifications outlined for them and explicitly disclaims all other warranties, whether express or implied, including but not limited to warranties of MERCHANTABILITY and FITNESS for a particular purpose.